



8/8/1.2

- Ø Backing Hole **16/16/10 or 16/16/12**
- Hole Size: **1.2mm**
- Type: **Round-Staggered**
- Distance Between the Holes: **8mm**
- Thickness Available: **12mm 15mm 18mm**

Standard melamine finish	• Beech, cherry, walnut, oak, maple, ash, pear, white, etc.
Standard wood veneer finish	• Beech, cherry, walnut, oak, maple, ash
Special finish	• On request
Base material	• Fire-resistant MDF & Not fire-resistant eco MDF
Special base material	• On request
Acoustic felt	• Black fleece glued on the back of the panel(optional)
Formats	• 600mmx1200mm,600mmx2400mm and custom
Tolerance	• Width +/- 0.3mm, Length +/- 0.3mm
Special finish	• On request

Product Sound Absorption Frequency and Coefficient

Siuperfo Clou 8/8/1.2 + 60K Fiberglass Acoustic Fleece

Freq. (Hz)	SAC. (50mm)	SAC. (200mm)
125	0.18	0.43
160	0.30	0.55
200	0.55	0.78
250	0.75	0.81
315	0.96	0.98
400	1.08	0.96
500	1.13	0.94
630	1.10	0.93
800	1.04	0.96
1K	1.03	1.00
1.25K	0.95	1.00
1.6K	0.91	0.95
2K	0.88	0.90
2.5K	0.81	0.87
3.15K	0.77	0.82
4K	0.74	0.80
5K	0.69	0.71

